



SML 100FA

1.0 m Flyaway Antenna

Satmission Model SML 100FA flyaway antenna is highly portable, compact, light-weight, and can be assembled by one person in less than 15 minutes. The antenna features a 7 piece segmented carbon fiber composite reflector designed to provide exceptional performance in a lightweight package.

The elevation-over-azimuth pedestal provides excellent stiffness characteristics and convenience for the user when pointing and peaking on a satellite. The antenna packs in 2 weatherized compression molded cases that meet the 62 inch rule for airline travel and are less than 32 Kg each.

In addition, the antenna is designed to meet international performance specifications for commercial or military applications and is readily available in X, Ku and/or Ka band frequencies.

Multiple feed configurations and paint schemes are readily available.



- Intelsat and Eutelsat Compliant
- Multi-Band C, X, Ku or Ka band Frequencies
- Multiple Integration Options
- Integrated Controller with Tracking Options Available
- Carbon Fiber Reinforced Polymer Structure – Lightweight and Stiff
- Low Profile and Space-Optimizing Stow Position
- Cable Drive Positioning System
- Superior Stability in Wind
- Excellent Reliability
- Minimal Maintenance

Technical Specifications

Electrical Specifications	2 Port X Band Circular		2 Port Cross Pol Ku Band Linear / Standard Feed		2 Port Cross Pol Ku Band Linear / Mode Matched Feed		2 Port Cross Pol Ka Band Circular Polarization	
	Rx	Tx	Rx	Tx	Rx	Tx	Rx	Tx
	Frequency (GHz)	7.25 - 7.75	7.9 - 8.4	10.70 - 12.75	13.75 - 14.5	10.95 - 12.75	13.75 - 14.5	20.2 - 21.2
Gain (Midband, dBi)	35.7	36.3	39.8	41.6	39.8	41.6	44.4	47.7
Noise Temperature (K)								
10 deg El	80		69		66		153	
20 deg El	65		59		58		102	
Axial Ratio	1.5 dB	1.5 dB					1.5 dB	1.0 dB
(low Axial Ratio Version)	0.5 dB	0.5 dB						
Cross Pol (std)								
On Axis	-21.3 dB	-21.3 dB	-35 dB	-35 dB	-35 dB	-35 dB	-21.3 dB	-24.8 dB
in 1 dB BW	-21.3 dB	-21.3 dB	-27 dB	-27 dB	-25 dB	-35 dB	-21.3 dB	-24.8 dB
Sidelobe Compliances	Meets DSCS		Meets ITU 580 FCC		ITU 580 Eutelsat		Meets ITU 580	
VSWR	1.30:1	1.30:1	1.35:1	1.30:1	1.50:1	1.30:1	1.35:1	1.30:1
Isolation								
Tx/Rx	-110 dB	0 dBm input	-85 dB	0 dBm input	-85 dB	0 dBm input	-85 dB	0 dBm input
Rx/Tx	0 dBm input	-110 dB	0 dBm input	-30 dB	0 dBm input	-30 dB	0 dBm input	-30 dB

Mechanical / Environmental Specifications	
Reflector	100 cm Carbon Fiber
Reflector Configuration	7 Piece Segmented Single Offset
Antenna Travel	
Azimuth	+/-180° continuous with fine adjust
Elevation	5 - 90° of reflector bore sight
Polarization	± 90°
Packaging (2 Cases)	
Pedestal Case (Compression Molded / Outdoor)	65 cm x 49,5 cm x 39,6 cm (21,7 kg)
Reflector Case (Compression Molded / Outdoor)	63,2 cm x 60,2 cm x 33,3 cm(23,6 kg)
RF Package - Per Band (Compression Molded / Outdoor)	Per RF Configuration
Temperature	
Operational	-30 to 60°C
Survival	-40 to 70°C
Winds	
Operational	48 kph Gusting to 72 kph
Survival (tied down, any position)	96 kph
Survival (tied down, stowed above 85 deg el.)	112 kph
Integration	
Feedboom Mounted ¹	11,33 Kg
Rain	
Operational	10 cm/h
Survival	15 cm/h
Relative Humidity	0 - 100%
Solar Radiation	1000 Kcal/h/m ²
Radial Ice (survival)	25.4 mm
Corrosive Atmosphere	As encountered in coastal and/or industrial areas

Note: Specifications subject to change without notice

¹ Dependent on mounting position relative to elevation axis

Satmission AB
 Bultenvägen 5
 S-95261 Kalix, Sweden
 Phone: +46 923 137 10
 E-mail: sales@satmission.com
 Web: www.satmission.com