



SML 200FA

2.0 m Flyaway Antenna

Satmission Model SML 200FA carbon fiber flyaway antenna offers superior performance in a lightweight, portable package.

This antenna features a 7 piece carbon fiber segmented reflector designed to provide high gain and low cross pol characteristics. The custom-designed elevation-over-azimuth tripod pedestal provides high stiffness with minimal weight.

The antenna components are modular in design which provides options for motorization and tracking requirements. High performance molded cases are included.

The antenna is designed to meet international performance specifications for commercial or off-the-shelf military applications and is readily available in C, X, Ku, DBS and Ka band frequencies. Multiple feed and integration packages are available with a quick change / quick pack configuration. The integrated boom assembly with BUC and LNB packs in a single case for quick installation.

Integrated feedbooms can be supplied which will allow a quick change from one frequency band to another.



- Intelsat & Eutelsat Compliant
- Multi-Band C, X, Ku, DBS and Ka Band Frequencies
- Integrated Feedboom Assembly Option
- Compact Packaging Packs in 4 Cases
- Captive Hardware – No Tools for Assembly
- Superior Stability in Wind
- Excellent Reliability
- Minimal Maintenance
- Less than 15 min Assembly Time
- Fully Motorized Configuration Available

Technical Specifications

Electrical Specifications	2 Port Cross-Pol C Band Extended Linear Feed		2 Port Cross-Pol C Band Std. Linear Feed		2 Port Cross-Pol C Band Circular Feed		2 Port X Band Circular Polarization		2 Port Cross-Pol Ku Band Linear / Mode Matched Feed	
	Rx	Tx	Rx	Tx	Rx	Tx	Rx	Tx	Rx	Tx
	Frequency (GHz)	3.40 - 4.20	5.85 - 6.725	3.625 - 4.2	5.85 - 6.425	3.625 - 4.2	5.85 - 6.425	7.25 - 7.75	7.9 - 8.4	10.95 - 12.75
Gain (Midband, dBi)	36.4	40.8	36.6	40.6	36.5	40.6	42.0	42.8	46.2	47.9
Noise Temperature (°K)										
10 deg EI	51		45		55		68		53	
20 deg EI	45		40		50		64		48	
Cross Pol										
On Axis	-30 dB	-30 dB	-30 dB	-30 dB	-20 dB	-27 dB	-30 dB	-30 dB	-35 dB	-35 dB
in 1 dB BW	-26 dB	-26 dB	-26 dB	-26 dB	-20 dB	-27 dB	-30 dB	-30 dB	-25 dB	-35 dB
Axial Ratio					1.6 dB	0.75 dB	0.5 dB	0.5 dB		
Sidelobe Compliances	Meets ITU 580 Beyond Mainbeam		Meets ITU 580 Beyond Mainbeam		Meets ITU 580 Beyond Mainbeam		Mil-Std 188-164A		ITU, FCC Eutelsat	
VSWR	1.40:1	1.30:1	1.30:1	1.30:1	1.35:1	1.30:1	1.30:1	1.30:1	1.35:1	1.30:1
Isolation										
Tx/Rx	-85 dB	0 dBm input	-85 dB	0 dBm input	-85 dB	0 dBm input	-120 dB	0 dBm input	-85 dB	0 dBm input
Rx/Tx	0 dBm input	-35 dB	0 dBm input	-35 dB	0 dBm input	-35 dB	0 dBm input	-120 dB	0 dBm input	-30 dB

Mechanical / Environmental Specifications

Reflector	2.0 meters Carbon Fiber
Reflector Configuration	Parabolic Single Offset, 0.8 F/D (7 pieces)
Antenna Travel	
Azimuth	360° continuous with fine adjust
Elevation	5 - 90° of reflector bore sight
Polarization	± 90°
Antenna Packaging	
Case 1 - Backbeam & Legs	114 cm x 64,3 cm x 42 cm (49,9 kg)
Case 2 - Az Hub, EI Strut, Foot Pads	95,3 cm x 70 cm x 37 cm (44,5 kg)
Case 3 & 4 - (7 piece reflector)	107 cm x 33 cm x 88 cm (38,5 kg ea.)
Total Weight (less feed options)	172 kg
Temperature	
Operational	-30 to 60°C
Survival	-40 to 70°C
Pointing Loss (operational winds)	3dB peak (Ku-band Rx)
Winds	
Operational	40 kph Gusting to 72 kph with ballast or anchors
Optional Wind Strut Accessory	72 kph
Survival	96 kph with tie downs / any position
Feedboom Mounted Integration	27.2 kg
Rain	
Operational	5 cm/h
Survival	10 cm/h
Relative Humidity	0 - 100% (condensing)
Solar Radiation	1000 Kcal/h/m ²
Radial Ice (survival)	12.7 mm
Corrosive Atmosphere	As encountered in coastal and/or industrial areas

Note: Specifications subject to change without notice

- * Feed packaged separately dependent on options ordered
- ** Performance dependent on proper installation and ballast/anchors
- *** Dependent on position of weight. Consult Engineering for details

Satmission AB
 Bultenvägen 5
 S-95261 Kalix, Sweden
 Phone: +46 923 137 10
 E-mail: sales@satmission.com
 Web: www.satmission.com